



MODEL	SR195HDA
Panel Type	19.5" (16:9) LED Backlit Monitor
Case Type	Plastic Case
Maximum Resolution	1920 x 1080
Active Display Area	434.88 (H) x 238.68 (V) mm
Pixel Pitch	0.2265 (H) x 0.221 (V) mm
Bezel Thickness	L/R/U: 17 mm, D:22.6 mm
Contrast Ratio	1000 : 1 Ratio
Brightness	250 cd/ m ²
Response Time	8m.sec (G2G)
Viewing Angle	178 /178
Display Colours	16.7 M
PC Compatible Frequency	30-60 KHz (H) / 56-75Hz (V)
Aspect Ratio	16 : 9 Ratio
VGA Auto Frequency correction	No
Speakers	2 x 3W
Number of Speakers	x 2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	5 % – 90 %
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	On/Off

MODEL		SR195HDA
IN/OUT INTERFACE		
Video Interface	HD-TVI (Supports 4Mp), HD-CVI (Supports 3Mp), AHD 2.0 (Supports 5Mp), x 1 BNC in /out, CVBS x 1, BNC in / out, HDMI x 1	
Audio Interface	PC Audio in / BNC Audio in Power Interface	
Power Interface	DC In x 1	
Termination	75 Ohms	
Stand Type	Desktop	
Safety & EMC Certification	CE, FCC, ROHS	
Vesa Standard Mount	100 x 100mm	
Colour	Black	
Button Position	Bottom, front of case	
Packing Dimension	540 x 120 x 395mm	
NET Weight	2.8 Kgs	
GROSS Weight	4.1 Kgs	
POWER		
Power Supply	12VDC, 3 amp	
Voltage	110 / 240v AC	
Power Consumption	18 watt(typical)	
OSD CONTROLS		
Contrast, Brightness, Colour Temperature, Sharpness, Anti-Picture-Burn-In, Sound volume, OSD position, OSD transparency, Background color, Factory reset		
OSD LANGUAGE		
English and Chinese		
ACCESSORIES		
HDMI Cable, User Manual, Power Adapter, Power Lead, Remote control		

