

MAIN FEATURES



2MP



1920 × 1080 Resolution



Up to 150m IR distance



4.8mm to 120mm, 25× Optical



IP66



24 VAC



| MODEL | SRSP25TVI2MP |
|------------------------------------|--|
| Image Sensor | 1/2.8" progressive scan CMOS |
| Max. Image Resolution | 1920 × 1080 |
| Frame Rate | 50Hz: 25fps @(1920 × 1080) 60Hz: 30fps @(1920 × 1080) |
| Min. Illumination | Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 lux with IR |
| White Balance | AUTO/MANUAL/HAUTO/ATW/INDOOR/OUTDOOR |
| AGC | AUTO/MANUAL |
| DNR | 3D DNR |
| WDR | ≥ 120 dB |
| Shutter Time | PAL: 1/1 s to 1/10,000 s NTSC: 1/1 s to 1/10,000 s |
| Day & Night | IR cut filter |
| Digital Zoom | 16x |
| Privacy Mask | 8 programmable privacy masks |
| BLC (Backlight Compensation) | YES |
| HLC (highlight Compensation) | YES |
| EIS (Electric Image Stabilization) | YES |
| Reginal Focus | YES |
| LENS | |
| Focus Mode | Auto/Semiauto/Manual |
| Focal Length | 4.8 mm to 120 mm, 25× Optical |
| Aperture Range | F 1.6 to F 3.5 |
| Field of View | Horizontal field of view: 57.6° to 2.5° (wide to tele) Vertical field of view: 34.4° to 1.4° (wide to tele) Diagonal field of view: 64.5° to 2.9° (wide to tele) |
| Min. Working Distance | 10 mm to 1500 mm (wide to tele) |
| Zoom Speed | Approx. 3.6 s (optical, wide to tele) |
| Pan and Tilt | |
| Pan Range | 360° endless |
| Pan Speed | Pan manual speed: 0.1° to 120°/s Pan preset speed: 120°/s |
| Tilt Range | -15° to 90° (auto flip) |



| MODEL | SRSP25TVI2MP |
|----------------------|--|
| Tilt Speed | Tilt manual speed: 0.1° to 80°/s Tilt preset speed: 80°/s |
| Proportional Zoom | Rotation speed can be adjusted automatically according to zoom multiples |
| Presets | 256 |
| Patrol | 10 patrols, up to 32 presets per patrol |
| Pattern | 5 patterns, with the total recording time no less than 10 minutes |
| Power-off Memory | Yes |
| Park Action | Preset/Patrol/Pattern/Pan Scan/Tilt Scan/Panorama Scan/Day Mode/Night |
| PTZ Position Display | ON/OFF |
| Preset Freezing | Yes |
| Scheduled Task | Preset/Patrol/Pattern/Pan Scan/Tilt Scan/Panorama Scan/Day Mode/Night Mode/Zero Calibration/None |
| Infrared | |
| IR Distance | Up to 150 m |
| IR Intensity | Automatically adjusted depending on the zoom ratio |
| Input/Output | |
| Alarm | 2 alarm inputs, 1 alarm output |
| RS-485 Interface | Half-duplex mode Self-adaptive, Pelco-P, Pelco-D protocol |
| UTC function | UTC protocol |
| General | |
| Menu Language | English |
| Power | 24 VAC Max.30 W (IR:10 W) |
| Mounting | Various mounting modes optional |
| Protection Level | IP66 standard outdoor dome TVS 4,000 V lightning protection surge protection and voltage transient protection |
| Mounting | Various mounting modes optional |
| Dimensions | Ø 208 mm . 305 mm (Ø 8.19" .12.01") |
| Weight (approx.) | 3.3 kg (7.28 lb.) |